

# SAFETY DATA SHEET S110 Original

According to Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice, December 2011

#### SECTION 1: Identification: Product identifier and chemical identity

**Product identifier** 

Product name S110 Original

Internal identification SNS110

Relevant identified uses of the substance or mixture and uses advised against

Application Non residual spot and stain remover for carpets, upholstery and drapes

**Uses advised against** Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Sonitron

42 Redcliffe Gardens Drive Clontarf, QLD, 4019 +61 7 3283 4511

Contact Person Poisons Information 131126 or Brennan Stark 0428 835 855

Manufacturer Eco Pro Australia Pty Ltd

42 Redcliffe Gardens Drive, Clontarf, QLD, 4019

+61 7 3283 4511

sampson\_office@bigpond.com

Emergency telephone number

**Emergency telephone** Poisons Information 131126 or Brennan Stark 0428 835 855

# SECTION 2: Hazard(s) identification

## Classification of the substance or mixture

Physical hazards Flam. Liq. 2 - H225

**Health hazards** Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304

**Environmental hazards** Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Label elements

Pictogram









Signal word

Danger

# S110 Original

Hazard statements H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361d CLP only - Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

#### Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/ shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

P321 Specific treatment (see medical advice on this label).

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/ attention.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

## Contains Toluene, heptane, Cyclohexane

#### Other hazards

This product does not contain any substances classified as PBT or vPvB.

#### SECTION 3: Composition and information on ingredients

#### **Mixtures**

Toluene	60-100%
CAS number: 108-88-3	
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
Repr. 2 - H361d	
STOT SE 3 - H336	
STOT RE 2 - H373	
Asp. Toy 1 - H304	

# S110 Original

heptane 30-60%

CAS number: 142-82-5

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Cyclohexane 10-30%

CAS number: 110-82-7

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

### Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical

personnel.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery

position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if

the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical attention. Do not induce vomiting. If vomiting occurs, the head should be kept low so that

vomit does not enter the lungs. Get medical attention immediately.

Skin Contact Rinse with water.

Eye contact Rinse with water. Get medical attention if any discomfort continues.

**Protection of first aiders** First aid personnel should wear appropriate protective equipment during any rescue.

**New category** 

Most important symptoms and effects, both acute and delayed

# S110 Original

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic

effect.

Ingestion May cause irritation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or

vomiting may cause chemical pneumonitis.

**Skin contact** Redness. Irritating to skin.

Eye contact No specific symptoms known. May be slightly irritating to eyes.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

#### SECTION 5: Firefighting measures

# Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

**Specific hazards**Containers can burst violently or explode when heated, due to excessive pressure build-up.

Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or

explosion hazard.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and

authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967

keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate

(for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.

Hazchem Code 3YE

# SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

# S110 Original

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be

taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of dust and

vapours. Use suitable respiratory protection if ventilation is inadequate.

**Environmental precautions** 

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the

aquatic environment.

#### Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills

immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into

drains. For waste disposal, see Section 13.

Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health

hazards. See Section 12 for additional information on ecological hazards. For waste disposal,

see Section 13.

#### SECTION 7: Handling and storage, including how the chemical may be safely used

#### Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Suspected of damaging the unborn child. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken

packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash

before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store locked up. Keep away from oxidising materials, heat and flames. Keep only in the

original container. Keep container tightly closed, in a cool, well ventilated place. Keep

containers upright. Protect containers from damage.

Storage class Flammable liquid storage.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls and personal protection

Control parameters

Occupational exposure limits

Toluene

# S110 Original

Long-term exposure limit (8-hour TWA): 50 ppm 191 mg/m<sup>3</sup> Short-term exposure limit (15-minute): 150 ppm 574 mg/m<sup>3</sup>

Sk

#### heptane

Long-term exposure limit (8-hour TWA): 400 ppm 1640 mg/m<sup>3</sup> Short-term exposure limit (15-minute): 500 ppm 2050 mg/m<sup>3</sup>

#### Cyclohexane

Long-term exposure limit (8-hour TWA): 100 ppm 350 mg/m<sup>3</sup> Short-term exposure limit (15-minute): 300 ppm 1050 mg/m<sup>3</sup>

Sk = Absorption through the skin may be a significant source of exposure.

#### **Exposure controls**

## Protective equipment





# Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.

#### Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

#### Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

# Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

#### Hygiene measures

Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

# Respiratory protection

Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with

Australia/New Zealand Standard AS/NZS 1716.

# **Environmental exposure** controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

**Appearance** Clear liquid. Colour Water-white.

# S110 Original

Odour Minimal/sweet odour

Specific Gravity 0.78

Flash point -10°C CC (Closed cup).

Vapour pressure <30 mm Hg @ 20°C

Solubility Value (g/100g H2O

Insoluble in water.

20°C)

## SECTION 10: Stability and reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidising agents.

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode

when heated, due to excessive pressure build-up. Static electricity and formation of sparks

must be prevented.

Materials to avoid Oxidising materials. Acids - oxidising.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

## SECTION 11: Toxicological information

# Information on toxicological effects

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>)

Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

# S110 Original

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable

as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the

result if vomited material containing solvents reaches the lungs.

General information Avoid contact during pregnancy/while nursing. The severity of the symptoms described will

vary dependent on the concentration and the length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic

effect.

Ingestion May cause irritation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or

vomiting may cause chemical pneumonitis.

**Skin Contact** Redness. Irritating to skin.

**Eye contact** No specific symptoms known.

Route of entry Ingestion Inhalation Skin and/or eye contact

Target Organs Central nervous system

SECTION 12: Ecological Information

**Toxicity** Aquatic Acute 1 - H400 Very toxic to aquatic life. Aquatic Chronic 1 - H410 Very toxic to

aquatic life with long lasting effects.

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bioaccumulative Potential No data available on bioaccumulation.

Mobility in soil

Mobility No data available.

Results of PBT and vPvB assessment

Other adverse effects

Other adverse effects None known.

# S110 Original

### **SECTION 13: Disposal considerations**

# Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product

residues and hence be potentially hazardous.

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal

contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

Incineration or landfill should only be considered when recycling is not feasible.

## **SECTION 14: Transport information**

General For limited quantity packaging/limited load information, consult the relevant modal

documentation using the data shown in this section.

**UN number** 

**UN No. (ADG)** 1268

**UN No. (IMDG)** 1268

UN No. (ICAO) 1268

UN proper shipping name

Proper shipping name (ADG) PETROLEUM DISTILLATES, N.O.S., or PETROLEUM PRODUCTS, N.O.S.

Proper shipping name

PETROLEUM DISTILLATES, N.O.S., or PETROLEUM PRODUCTS, N.O.S. (CONTAINS

(IMDG)

heptane, Cyclohexane)

Proper shipping name (ICAO) PETROLEUM DISTILLATES, N.O.S., or PETROLEUM PRODUCTS, N.O.S.

## Transport hazard class(es)

ADG class 3

ADG classification code F1

ADG label 3

IMDG class 3

ICAO class/division 3

# Transport labels



# Packing group

ADG packing group

IMDG packing group

ICAO packing group

**Environmental hazards** 

# S110 Original

#### Environmentally hazardous substance/marine pollutant



#### Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-E, S-E

Hazchem Code 3YE

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

#### SECTION 15: Regulatory information

# Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Inventories

Australia - AICS

None of the ingredients are listed or exempt.

#### SECTION 16: Any other relevant information

**Training advice** Only trained personnel should use this material.

Revision date 26/07/2016

Revision 1

**SDS No.** 5049

General Information The following risk and hazard statements are to be considered a glossary. They relate to the

raw materials used in this product and therefore may not be accurate for the finished product itself. For the complete risk and hazard statements for this product please refer to section 2 of

this Safety Data Sheet

Hazard statements in full H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361d CLP only - Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.